

Automotive Collection

Automotive Collection

Morbern Automotive Collection

Allante • Corinthian • Edge • G-Grain
Heidi • Longitude • Madrid • Milled Pebble
Montana • Monticello • Oxen • Rawhide
Rush • Shock • Sierra • Toyota • Volans
Wallaby • Wave

Pattern	Roll Width	Roll Size (Yds.)	Quality	Weight per Linear Yard. (approx.)	Cold Crack	Adhesion of Coating ASTM D751 Excellent	Tear Strength Fed. Std. 191-51.36 Excellent	Tensile Strength ASTM D751 Excellent	Abrasion Resistance using the Wyzenbeek Method	Ultraviolet Stable Pigment	1000 Hour Weathermeter	Mildew Resistant	Oil Resistant	FMVSS-302	California Fire Code 117	UFAC Class 1	BIFMA Class 1
Allante	54"	40	Mellotech MR/FR	29.25 ± 1.5	-25°F	●	●	●	100,000 Double Rubs	●	●	●	●	●	●	●	●
Corinthian	54"	40	Mellohide	32 ± 1.6	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Edge	54"	40	Merritt MR/FR	30.75 ± 1.25	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
G-Grain	54"	40	Mellohide	32 ± 1.6	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Heidi	61"	40	Mellohide	32 ± 1.6	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Longitude	54"	40	Mellotech MR/FR+	30.75 ± 1.5	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Madrid	54"	40	Mellohide	32 ± 1.6	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Milled Pebble	54"	40	Mellotech MR/FR+	30.75 ± 1.5	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Montana	54"	40	Mellohide	32 ± 1.6	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Monticello	54"	40	Mellohide	32 ± 1.6	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Oxen	54"	40	Mellohide	32 ± 1.6	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Rawhide	54"	40	Mellohide	32 ± 1.6	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Rush	54"	40	Merritt MR/FR	30.75 ± 1.25	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Shock	54"	40	Merritt MR/FR	30.75 ± 1.25	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Sierra	54"	40	Mellohide	32 ± 1.6	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Toyota	54"	40	Mellohide	32 ± 1.6	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Volans	54"	40	Mellotech MR/FR+	30.75 ± 1.5	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Wallaby	54"	40	Mellohide	32 ± 1.6	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●
Wave	54"	40	Merritt MR/FR	30.75 ± 1.25	-25°F	●	●	●	30,000 Double Rubs	●	●	●	●	●	●	●	●

All flammability specifications and all corresponding data refer to typical performance in the specific test indicated and should not be construed to imply the behavior of those or any other material under actual fire conditions.

This information is offered for your general guidance only. It is accurate to the best of our knowledge at the time of printing, but is not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with the laws and procedures applicable to the safe handling and use of this material.

Care and Cleaning Instructions

For Normal Cleaning: In general, most common stains can be cleaned using warm, soapy water and clear water rinses. Moderate scrubbing with a medium bristle brush will help to loosen soiling material from the depressions of embossed surfaces.

For Stubborn Stains: Use Formula 409® commercially available mild detergent in accordance with manufacturers' instructions. Test cleaners in an inconspicuous area as cleaner manufacturers may change formulas without notice. Full strength rubbing alcohol or mineral spirits may be tried cautiously as a last resort on very stubborn stains, if the above suggestions do not work. Indiscriminate use of any solvent or solvent containing cleaner can severely damage or discolor vinyls.

Imprint Area

Job: 3314 Date: 02/11/10 v.2 pm
Case for Mockup
Note: Colors on this proof do not represent actual color.
■ = Black + Soft Matte Mylar
■ = Toyo 10098
OK'd by:
Date:
This proof must be OK'd by our customer's authorized agent. Production cannot be started until it is returned. Final responsibility for copy, spelling, grammar, placement, punctuation, etc., will rest on you, the customer. Changes at this point may result in extra charges. Please mark any changes clearly on this proof.
All proofs remain the property of: Leed Selling Tools Corp.